

**Amendments to Claims**

This listing of claims will replace all prior revisions and listings of claims in this application.

**Listing of Claims**

- 1 1. (Currently Amended) A method comprising:  
2 generating a phase-shift keyed optical signal; and  
3 propagating the phase shift keyed optical signal through a semiconductor optical  
4 amplifier in deep saturation such that an optical signal exhibiting a regulated, ~~to~~  
5 regulate the amplified optical power is produced.
- 1 2. (Previously presented) The method of claim 1, wherein the amplified optical power is  
2 regulated to about the saturation output power of the semiconductor optical amplifier.
- 1 3. (Currently Amended) The method of claim 1, wherein ~~the~~ a gain recovery time of the  
2 optical amplifier is larger than the bit period of the optical signal.
- 1 4. (Original) The method of claim 1, wherein the optical signal has a data-independent  
2 intensity profile.
- 1 5. (Original) The method of claim 1 wherein the optical signal is RZ-DPSK signal.
- 1 6. (Original) The method of claim 1, wherein the optical signal is an  $\pi/2$ -DPSK signal.
- 1 7. (Original) The method of claim 1, wherein the optical signal is a constant-intensity DPSK  
2 signal.

- 1 8. (Original) The method of claim 1, wherein the optical signal is an RZ-DQPSK signal.
- 1 9. (Original) The method of claim 1, wherein  $\Delta P_{OUT}(dB)/\Delta P_{IN}(dB)$  of the optical amplifier is  
2 less than about 0.25, wherein  $P_{OUT}$  is the power of the optical signal output from the  
3 amplifier, and  $P_{IN}$  is the power of the optical signal input into the amplifier.
- 1 10. (Currently Amended) A method for optical limiting amplification comprising:  
2 ~~propagating~~ inputting a phase-shift keyed optical signal having a data independent  
3 intensity profile ~~through~~ into a semiconductor optical amplifier such that an optical  
4 signal exhibiting a regulated, amplified optical power is produced and output,  
5 wherein  $\Delta P_{OUT}(dB)/\Delta P_{IN}(dB)$  is less than about 0.25, ~~to regulate the amplified~~  
6 optical power, where  $P_{OUT}$  is the power of the optical signal output from the  
7 amplifier, and  $P_{IN}$  is the power of the optical signal input into the amplifier.
- 1 11. (Currently Amended) The method of claim 10, wherein ~~the~~ a gain recovery time of the  
2 optical amplifier is larger than the bit period of the optical signal.
- 1 12. (Original) The method of claim 10, wherein the optical signal is an RZ-DPSK signal.
- 1 13. (Original) The method of claim 10, wherein the optical signal is an  $\pi/2$ -DPSK signal.
- 1 14. (Original) The method of claim 10, wherein the optical signal is a constant-intensity  
2 DPSK signal.
- 1 15. (Original) The method of claim 10, wherein the optical signal is an RZ-DQPSK signal.
- 1 16. (Withdrawn) A channel power equalizer comprising:

- 2 a demultiplexer for demultiplexing an optical signal into a plurality of channels, each said  
3 channels having a different optical wavelength;
- 4 a plurality of semiconductor optical amplifiers optically coupled to the demultiplexer for  
5 separately providing optical amplification to the respective ones of the plurality of  
6 channels; and
- 7 a multiplexer coupled to each one of the plurality of semiconductor optical amplifiers, for  
8 multiplexing the plurality of optical channels,
- 9 such that each one of the plurality of optical channels in the multiplexed signal has  
10 substantially equal optical power.

1 17. (Original) An optical signal processor apparatus comprising:

- 2 a semiconductor optical amplifier device adapted to operate in deep saturation and to  
3 receive an RZ-DPSK optical signal having an amplitude-shift keyed optical label  
4 portion, such that the optical label portion of the signal is removed upon propagation  
5 through the semiconductor optical amplifier device.

1 18. (Withdrawn) An optical add/drop multiplexer device comprising:

- 2 a demultiplexer for demultiplexing a multi-channel wavelength-division multiplexed  
3 phase shift keyed optical signal into a plurality of optical channels, each said  
4 channels having a different optical wavelength;
- 5 a multiplexer having a plurality of input ports, for multiplexing at least one of the  
6 plurality of optical channels received from the demultiplexer and at least one added  
7 channel; and
- 8 a plurality of semiconductor optical amplifiers optically coupled to each one of input  
9 ports of the multiplexer, wherein the plurality of semiconductor optical amplifiers are  
10 adapted to separately suppress transient optical power fluctuations in each one of the  
11 plurality of the optical channels, and provide optical power equalization between the  
12 plurality of optical channels to be multiplexed.

1 19. (Original) An optical communication system for transmitting multi-channel phase-shift keyed  
2 optical signals comprising:

3 a plurality of semiconductor optical amplifiers,

4 wherein the system is adapted to transmit the optical signals such that the plurality of  
5 semiconductor optical amplifiers operate in deep saturation so as to provide optical power  
6 equalization of a plurality of channels of the multi-channel optical signals.

1 20. (Original) An apparatus comprising:

2 a means for generating a phase-shift keyed optical signal; and

3 a means for propagating the optical signal through a semiconductor optical amplifier in deep  
4 saturation to regulate the amplified optical power.